Application

Compact performance floodlight with 1/2" I.P.S. nipple for use with a variety of mounting accessories. Designed to spotlight architectural features, landscaping or signage. Pair with a variety of optical accessories.

Materials

Clear safety glass

Marine grade, copper free (≤ 0.3% copper content) A360.0 aluminum alloy High temperature silicone gasket

Silicone applied robotically to casting, plasma treated for increased adhesion

316 stainless steel 1/2" IPS threaded nipple Pure anodized aluminum reflector surface BEGA Hybrid Optics®

NRTL listed to North American Standards, suitable for wet locations

Protection class IP 65

Weight: 9.3 lbs.

EPA (Effective projection area): 0.38 sq. ft.

Electrical

Operating voltage 120-277V AC Minimum start temperature LED module wattage 25.6 W System wattage 32.0 W

Controllability 0-10V, TRIAC, and ELV dimmable

Color rendering index Ra > 80 Luminaire lumens 1055 lm LED service life (L70) 60000 hrs

LED color temperature

4000K (K4) 3500K (K35) 3000K (K3) 2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish, a fluoropolymer technology, provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL and custom color finishes provided in either polyester powder or liquid paint.

Available colors

Black (BLK) Bronze (BRZ)
Silver (SLV) White (WHT)
RAL: CUS:



Performance floodlight · Very narrow beam

	LED		А	В	С	
B84359	25.6W	5°	81/,	121/	51/,	

Type:

BEGA Product:

Project: Modified:

Available options

CUS Custom finish FSC Fusing

MGU Marine grade undercoat

RAL RAL finish

Available accessories

7.17.41.14.21.17.17.17.17.17.17.17.17.17.17.17.17.17				
B19593	Surface mount conduit wiring box			
B19594	Direct burial wiring box			
B70204	Earth spike			
B70249	Pole cap · 3" O.D. pole tenon			
B70252	Wood screw			
B70280	Tube clamp			
B70283	Screw clamp			
B70379	Pole mount arm · 1/2" I.P.S. nipple floodlights			
B71042	Pole coupler			
B71121	Glare shield · 180°			
B79511	Mounting block			
B79831	Glare shield · 360°			

See individual accessory spec sheet for details.

