

**Application**

Pole-top luminaire with symmetric light distribution ideal for illuminating squares, plazas and other open spaces. Provided with slip fitter to fit 3" O.D. poles.

**Materials**

Clear safety glass  
 Marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy  
 Mechanically captive stainless steel fasteners  
 High temperature silicone gasket  
 Pure anodized aluminum reflector

**NRTL** listed to North American Standards, suitable for wet locations  
 Protection class IP 65

**Weight:** 32.2 lbs.

**EPA (Effective projection area):** 1.5 sq. ft.

**Electrical**

Operating voltage 120-277V AC  
 Minimum start temperature -30° C  
 LED module wattage 47.4 W  
 System wattage 56.0 W  
 Controllability 0-10V dimmable  
 Color rendering index Ra > 80  
 Luminaire lumens 3695 lm  
 LED service life (L70) 60000 hrs

**LED color temperature**

- 4000K (K4)
- 3500K (K35)
- 3000K (K3)
- 2700K (K27)


**BEGA** can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

**Finish**

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish, a fluoropolymer technology, provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL and custom color finishes provided in either polyester powder or liquid paint.

**Available colors**

- Black (BLK)
- Silver (SLV)
- RAL:
- Bronze (BRZ)
- White (WHT)
- CUS:



**Pole-top luminaire · Symmetric**

	LED	A	B
<b>B84402</b>	47.4 W	28	14 1/4

Type:  
 BEGA Product:  
 Project:  
 Modified:

**Available options**

- CUS Custom finish
- FSC Fusing
- MGU Marine grade undercoat
- RAL RAL finish

