# Application

Compact performance floodlight with mounting canopy for mounting to horizontal or vertical surfaces. Designed to spotlight architectural features, landscaping or signage. Pair with a variety of optical accessories.

#### Materials

Clear safety glass

Marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy

High temperature silicone gasket

Mechanically captive stainless steel fasteners Pure anodized aluminum reflector surface

Composite concentric ring louver

BEGA Hybrid Optics®

NRTL listed to North American Standards, suitable for wet locations

Protection class IP 65

Weight: 6.2 lbs.

EPA (Effective projection area): 0.32 sq. ft.

### Electrical

120-277VAC Operating voltage Minimum start temperature -30° C LED module wattage 12.8W 18.0W System wattage

Controllability 0-10V, TRIAC, and ELV dimmable

Color rendering index Ra > 80Luminaire lumens 518 lm LED service life (L70) 60000 hrs

## LED color temperature

4000K (K4) 3500K (K35) 3000K (K3) 2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish, a fluoropolymer technology, provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL and custom color finishes provided in either polyester powder or liquid paint.

### Available colors

Black (BLK) Bronze (BRZ) Silver (SLV) White (WHT) RAL: CUS:

# Performance floodlights · Very narrow beam

	LED		Α	В	С	D	
B84408	12.8W	5°	67/.	101/0	5	4	

Type:

**BEGA Product:** 

Project: Modified:

# Available options

CUS Custom finish **FSC** Fusina

MGU Marine grade undercoat

RAL RAL finish

# Available accessories

B71111 Glare shield · 180° B79830 Glare shield · 360°

See individual accessory spec sheet for details.

