Application

Compact performance floodlight with 1/2" I.P.S. nipple for use with a variety of mounting accessories. Designed to illuminate architectural features, landscaping, signage, and for general illumination of a space. Pair with a variety of optical accessories.

Materials

Clear safety glass

Marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy Silicone applied robotically to casting, plasma treated for increased adhesion

High temperature silicone gasket Mechanically captive stainless steel fasteners 316 stainless steel 1/2" IPS threaded nipple Pure anodized aluminum reflector surface

BEGA Hybrid Optics®

NRTL listed to North American Standards, suitable for wet locations

Protection class IP 65

Weight: 11.9 lbs. EPA (Effective projection area): 0.5 sq. ft.

Electrical

LED module wattage 71.1 W
System wattage 77.0 W
Color rendering index Ra > 90
Luminaire lumens 8086 lm
LED service life (L70) 60000 hrs

LED color temperature

4000K (K4) 3500K (K35) 3000K (K3) 2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish, a fluoropolymer technology, provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL and custom color finishes provided in either polyester powder or liquid paint.

Available colors

 Black (BLK)
 Bronze (BRZ)

 Silver (SLV)
 White (WHT)

 RAL:
 CUS:

Project:

Type:

Modified:

BEGA Product:

Available options

B71073 Concentric ring louver
B71074 Elliptical spread lens
CUS Custom finish
FSC Fusing

MGU Marine grade undercoat


RAL RAL finish

Available accessories

Ŀ	319593	Surface mount conduit wiring box
Е	319594	Direct burial wiring box
Е	370204	Earth spike
Е	370249	Pole cap · 3" O.D. pole tenon
Е	370252	Wood screw
Е	370280	Tube clamp
Е	370283	Screw clamp
Е	370379	Pole mount arm · 1/2" I.P.S. nipple floodlights
Е	371042	Pole coupler
Е	371072	Glare shield · 180°
Е	379511	Mounting block

See individual accessory spec sheet for details.





Performance floodlight · Narrow beam

	LED		Α	В	С
B84548	71.1 W	28°	97/8	13 ³ / ₄	51/2