

Application
Bollard luminaire with unshielded symmetric light distribution. These robust luminaires can delineate and structure outside areas. Provided with mounting system that allows the luminaire to be adjusted independent of anchor bolt orientation.

Materials
White UV-stabilized acrylic diffuser
Die-cast aluminum
Extruded aluminum
Mechanically captive stainless steel fasteners
High temperature silicone gasket
Galvanized steel anchorage

NRTL listed to North American Standards, suitable for wet locations
Protection class IP 65

Weight: 15.5 lbs.

Electrical
Operating voltage 120-277V AC
Minimum start temperature -30° C
LED module wattage 15.6 W
System wattage 19.0 W
Controllability 0-10V dimmable
Color rendering index Ra > 80
Luminaire lumens 1939 lm
LED service life (L70) 60000 hrs

LED color temperature
4000K (K4)
3500K (K35)
3000K (K3)
2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details


Finish
All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish, a fluoropolymer technology, provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL and custom color finishes provided in either polyester powder or liquid paint.

Available colors
Black (BLK) Bronze (BRZ)
Silver (SLV) White (WHT)
RAL: CUS:

Type:
BEGA Product:
Project:
Modified:

Available options
CUS Custom finish
FSC Fusing
MGU Marine grade undercoat
RAL RAL finish

Included (available for pre-shipment)
B79817 Anchorage kit



Bollard · Unshielded with safety guard			
	LED	A	B
B84602	15.6 W	6 1/4	33 1/2

