# Application

Pathway luminaire with unshielded light for use in the private sector. These luminaires are ideally suited for gardens, entryways, and for many applications on paths and terraces. Anchorage unit is intended for direct burial in concrete or soil. Low voltage magnetic transformer required for operation.

#### Materials

Pressed crystal glass with white ceramic coating on one side Marine grade, copper free (≤ 0.3% copper content) A360.0 aluminum alloy High temperature silicone gasket Mechanically captive stainless steel fasteners

NRTL listed to North American Standards, suitable for wet locations Protection class IP 65

Weight: 10.0 lbs.

Galvanized steel anchorage

#### Electrical

Operating voltage 12VAC
Minimum start temperature -40° C
LED module wattage 2.9W
System wattage 4.4W
Controllability Non-Di

Controllability

Color rendering index

Luminaire lumens

LED service life (L70)

Non-Dimming

Ra > 90

262 lm

60000 hrs

## LED color temperature

4000K (K4) 3500K (K35) 3000K (K3) 2700K (K27)

**BEGA** can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

### Finish

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish, a fluoropolymer technology, provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL and custom color finishes provided in either polyester powder or liquid paint.

## Available colors

Black (BLK) Bronze (BRZ)
Silver (SLV) White (WHT)
RAL: CUS:



Garden bollard · Direct burial anchorage • 12V AC			
	LED	А	В
B84605	2.9W	43/4	313/。

Type:

**BEGA Product:** 

Project: Modified:

#### Available options

CUS Custom finish

MGU Marine grade undercoat

RAL RAL finish

# Available accessories

B536 Low voltage magnetic transformer · 300W

See individual accessory spec sheet for details.

