Application

Bollard luminaire with indirect light distribution. The light is directed onto the top reflector and then redirected downward onto the illuminated surface. These luminaires are ideal where glare-free illumination is required. Provided with mounting system that allows the luminaire to be adjusted independent of anchor bolt orientation.

Materials

Borosilicate glass
Die-cast aluminum
Extruded aluminum
Mechanically captive

Mechanically captive stainless steel fasteners

High temperature silicone gasket Galvanized steel anchorage

Pure anodized aluminum reflector

NRTL listed to North American Standards, suitable for wet locations

Protection class IP 65

Weight: 25.2 lbs.

Electrical

Operating voltage 120-277V AC
Minimum start temperature -30° C
LED module wattage 36.3 W
System wattage 40.5 W

Controllability 0-10V, TRIAC, and ELV dimmable

Color rendering index Ra > 80 Luminaire lumens 1694 lm LED service life (L70) 60000 hrs

LED color temperature

4000K (K4) 3500K (K35) 3000K (K3) 2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish, a fluoropolymer technology, provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL and custom color finishes provided in either polyester powder or liquid paint.

Available colors

Black (BLK) Bronze (BRZ)
Silver (SLV) White (WHT)
RAL: CUS:



Bollard ⋅ Directed light				
	LED	Α	В	С
B84610	36.3 W	131/2	433/8	61/2

Type:

BEGA Product:

Project: Modified:

Available options

CUS Custom finish

FSC Fusing

MGU Marine grade undercoat

RAL RAL finish

Included (available for pre-shipment)

B79817 Anchorage kit

