

Application

Bollard with unshielded symmetric light distribution. Designed for landscapes, pathways, and open spaces, these robust luminaires can delineate and structure exterior spaces. Provided with mounting system that allows the luminaire to be adjusted independent of anchor bolt orientation.

Materials

- White UV-stabilized acrylic diffuser
- Die-cast aluminum
- Extruded aluminum
- High temperature silicone gasket
- Mechanically captive stainless steel fasteners

NRTL listed to North American Standards, suitable for wet locations
Protection class IP 65

Weight: 21.4 lbs.

Electrical

- Operating voltage120-277V AC
- Minimum start temperature-30° C
- LED module wattage24.8 W
- System wattage27.5 W
- Controllability0-10V, TRIAC, and ELV dimmable
- Color rendering indexRa > 80
- Luminaire lumens2001 lm
- LED service life (L70)60000 hrs

LED color temperature

- 4000K (K4)
- 3500K (K35)
- 3000K (K3)
- 2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish, a fluoropolymer technology, provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL and custom color finishes provided in either polyester powder or liquid paint.

Available colors

- | | |
|--------------|--------------|
| Black (BLK) | Bronze (BRZ) |
| Silver (SLV) | White (WHT) |
| RAL: | CUS: |

Type:
BEGA Product:
Project:
Modified:

Available options

- | | |
|-----|------------------------|
| CUS | Custom finish |
| FSC | Fusing |
| MGU | Marine grade undercoat |
| RAL | RAL finish |

Included (available for pre-shipment)

- | | |
|--------|---------------|
| B79817 | Anchorage kit |
|--------|---------------|



Bollard · Unshielded with safety guard			
	LED	A	B
B84667	24.8 W	6 1/4	43 1/2

