

Application

Bollard luminaire with unshielded light distribution that provides brilliant illumination of ground surfaces as well as high levels of vertical illuminance perfect for illuminating people or architectural elements.

Materials

Clear safety glass with white ceramic coating
 Marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy
 High temperature silicone gasket
 Self-expanding sleeve anchors for pre-cast concrete
 Pure anodized aluminum reflector

NRTL listed to North American Standards, suitable for wet locations
 Protection class IP 65

Weight: 18.0lbs.

Electrical

Operating voltage 120-277V AC
 Minimum start temperature -30° C
 LED module wattage 12.3 W
 System wattage 14.5 W
 Controllability 0-10V dimmable
 Color rendering index Ra > 90
 Luminaire lumens 907 lm
 LED service life (L70) 60000 hrs

LED color temperature

- 4000K (K4)
- 3500K (K35)
- 3000K (K3)
- 2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish, a fluoropolymer technology, provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL and custom color finishes provided in either polyester powder or liquid paint.

Available colors

- Black (BLK)
- Silver (SLV)
- RAL:
- Bronze (BRZ)
- White (WHT)
- CUS:



Bollard · Unshielded

	LED	A	B	C
B84669	12.3W	13 ³ / ₈	15 ³ / ₄	4

Type:

BEGA Product:

Project:

Modified:

Available options

- CUS Custom finish
- FSC Fusing
- MGU Marine grade undercoat
- RAL RAL finish

