

**Application**

On-ground luminaire for illuminating horizontal surfaces from very low mounting heights such as squares, entrances and wide pathways. Provided with mounting system that allows the luminaire to be adjusted independent of anchor bolt orientation.

**Materials**

Clear safety glass with optical texture  
 Marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy  
 High temperature silicone gasket  
 Mechanically captive stainless steel fasteners  
 Galvanized steel anchorage  
 Pure anodized aluminum reflector

**NRTL** listed to North American Standards, suitable for wet locations  
 Protection class IP 67

**Weight:** 5.8 lbs.

**Electrical**

Operating voltage 120-277V AC  
 Minimum start temperature -30° C  
 LED module wattage 16.4 W  
 Controllability 0-10V dimmable  
 Color rendering index Ra > 80  
 Luminaire lumens 712 lm  
 LED service life (L70) 60000 hrs

**LED color temperature**

4000K (K4)  
 3500K (K35)  
 3000K (K3)  
 2700K (K27)

**BEGA** can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

**Finish**

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish, a fluoropolymer technology, provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL and custom color finishes provided in either polyester powder or liquid paint.

**Available colors**

Black (BLK) Bronze (BRZ)  
 Silver (SLV) White (WHT)  
 RAL: CUS:

Type:


BEGA Product:

Project:

Modified:

**Available options**

CUS Custom finish  
 FSC Fusing  
 MGU Marine grade undercoat  
 RAL RAL finish



**On-ground surface washer · Asymmetric**

	LED	A	B	C
<b>B84815</b>	16.4 W	9	6 <sup>3</sup> / <sub>4</sub>	7 <sup>1</sup> / <sub>8</sub>

