

**Application**

Bollard with 360° light distribution in stainless steel. This luminaire is designed to illuminate paths, entrances and driveways in private and public areas.

**Materials**

Chemically hardened soda-lime glass  
 Corrosion-resistant 304 grade stainless steel  
 Zinc plated carbon steel anchor bolts with template  
 Pure anodized aluminum reflector

**NRTL** listed to North American Standards, suitable for wet locations  
 Protection class IP 65

**Weight:** 38.6lbs.

**Electrical**

Operating voltage 120-277VAC  
 Minimum start temperature -30° C  
 LED module wattage 16.5W  
 System wattage 19.0W  
 Controllability 0-10V dimmable  
 Color rendering index Ra > 80  
 Luminaire lumens 1481 lm  
 LED service life (L70) 60000hrs

**LED color temperature**

- 4000K (K4)
- 3500K (K35)
- 3000K (K3)
- 2700K (K27)

**BEGA** can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

**Finish**

#4 brushed stainless steel. Custom colors are not available.

Type:

BEGA Product:

Project:

Modified:

**Included (available for pre-shipment)**

B79818 Anchorage kit



**Bollard · Shielded with reflector · 360°**

	LED	A	B	C
<b>B88061</b>	16.5W	8 <sup>1</sup> / <sub>8</sub>	43 <sup>7</sup> / <sub>8</sub>	11 <sup>7</sup> / <sub>8</sub>