

Application

Light building elements are luminous design features for public areas. These luminaires are ideally suited for delineating and structuring interior and exterior spaces such as landscape areas, plazas, building entrances, and atria. DarkSky Approved (2700K and 3000K only).

Materials

- Optically textured UV-stabilized acrylic diffuser
- Die-cast aluminum
- Extruded aluminum pole shaft
- Marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy
- High temperature silicone gasket
- Mechanically captive stainless steel fasteners
- Pure anodized aluminum reflector

NRTL listed to North American Standards, suitable for wet locations
Protection class IP 65

Weight: 77.6lbs.

EPA (Effective projection area): 11.8 sq. ft.

Electrical

- Operating voltage120-277VAC
- Minimum start temperature-40° C
- LED module wattage31.0W
- System wattage36.0W
- Controllability0-10V dimmable
- Color rendering indexRa > 80
- Luminaire lumens3279lm
- LED service life (L70)60000hrs

LED color temperature

- 4000K (K4)
- 3500K (K35)
- 3000K (K3) [DarkSky Approved]
- 2700K (K27) [DarkSky Approved]

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish, a fluoropolymer technology, provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL and custom color finishes provided in either polyester powder or liquid paint.

Available colors

- Black (BLK)

Silver (SLV)

RAL:
- Bronze (BRZ)

White (WHT)

CUS:

Type:

BEGA Product:

Project:

Modified:

Available options

- 347V

CUS

FSC

MGU

RAL
- 347V input

Custom finish

Fusing

Marine grade undercoat

RAL finish



Building element · Asymmetric

	LED	A	B	C	D
B88067	31.0W	6 ⁵ / ₈	23 ⁵ / ₈	177	31 ¹ / ₂

