

**Application**

Pole-top luminaire with symmetric light distribution and shallow height. The uniform distribution is ideal for illuminating squares, plazas and other open areas.

**Materials**

White UV-stabilized acrylic diffuser  
 Marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy  
 High temperature silicone gasket

**NRTL** listed to North American Standards, suitable for wet locations  
 Protection class IP 65

**Weight:** 12.4 lbs.

**EPA (Effective projection area):** 0.7 sq. ft.

**Electrical**

Operating voltage	120, 220-240 OR 277 VAC
Minimum start temperature	-30° C
LED module wattage	16.8 W
System wattage	28.6 W
Controllability	0-10V dimmable
Color rendering index	Ra > 80
Luminaire lumens	1716 lm
LED service life (L70)	60000 hrs

**LED color temperature**

- 4000K (K4)
- 3500K (K35)
- 3000K (K3)
- 2700K (K27)


**BEGA** can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

**Finish**

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish, a fluoropolymer technology, provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL and custom color finishes provided in either polyester powder or liquid paint.

**Available colors**

- |              |              |
|--------------|--------------|
| Black (BLK)  | Bronze (BRZ) |
| Silver (SLV) | White (WHT)  |
| RAL:         | CUS:         |



**Pole-top luminaire · Symmetric**

	LED	A	B
<b>B88100</b>	16.8 W	24 1/4	5 1/2

Type:

BEGA Product:

Project:

Modified:

**Available options**

- |     |                        |
|-----|------------------------|
| CUS | Custom finish          |
| FSC | Fusing                 |
| MGU | Marine grade undercoat |
| RAL | RAL finish             |

