

Application

Pole-top luminaire with symmetric light distribution and shallow height. The uniform distribution is ideal for illuminating squares, plazas and other open areas.

Materials

White UV-stabilized acrylic diffuser
 Marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy
 High temperature silicone gasket

NRTL listed to North American Standards, suitable for wet locations
 Protection class IP 65

Weight: 13.2 lbs.

EPA (Effective projection area): 0.7 sq. ft.

Electrical

Operating voltage 120, 220-240 OR 277 VAC
 Minimum start temperature -30° C
 LED module wattage 25.2 W
 System wattage 30.0 W
 Controllability 0-10V dimmable
 Color rendering index Ra > 80
 Luminaire lumens 2531 lm
 LED service life (L70) 60000 hrs

LED color temperature

- 4000K (K4)
- 3500K (K35)
- 3000K (K3)
- 2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish, a fluoropolymer technology, provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL and custom color finishes provided in either polyester powder or liquid paint.

Available colors

- | | |
|--------------|--------------|
| Black (BLK) | Bronze (BRZ) |
| Silver (SLV) | White (WHT) |
| RAL: | CUS: |

Type:


BEGA Product:

Project:

Modified:

Available options

- | | |
|-----|------------------------|
| CUS | Custom finish |
| FSC | Fusing |
| MGU | Marine grade undercoat |
| RAL | RAL finish |



Pole-top luminaire · Symmetric

	LED	A	B
B88164	25.2 W	24 1/4	5 1/2

