

Application

An edge-lit luminaire designed with exquisite visual interest for the illumination of walkways and open pedestrian landscape areas.

Materials

- Optically textured UV-stabilized acrylic diffuser
- Die-cast aluminum
- Extruded aluminum pole shaft
- High temperature silicone gasket
- Stainless steel hardware
- Pure anodized aluminum reflector

NRTL listed to North American Standards, suitable for wet locations
Protection class IP 65

Weight: 62.6 lbs.

Electrical

- Operating voltage120-277V AC
- Minimum start temperature-30° C
- LED module wattage23.2 W
- System wattage38.0 W
- Controllability0-10V dimmable
- Color rendering indexRa > 80
- Luminaire lumens2591 lm
- LED service life (L70)60000 hrs

LED color temperature

- 4000K (K4)
- 3500K (K35)
- 3000K (K3)
- 2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish, a fluoropolymer technology, provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL and custom color finishes provided in either polyester powder or liquid paint.

Available colors

- Black (BLK)
- Silver (SLV)
- RAL:
- Bronze (BRZ)
- White (WHT)
- CUS:

Type:
BEGA Product:
Project:
Modified:

Available options

- CUSCustom finish
- MGUMarine grade undercoat
- RALRAL finish



Light building element · Asymmetric wide beam					
	LED	A	B	C	D
B88166	23.2 W	20 1⁄8	21 5⁄8	153 7⁄8	31 1⁄2

