

**Application**

Pole-top luminaire with symmetric light distribution and shallow height. The symmetric light distribution is ideal for illuminating squares, plazas and other open areas.

**Materials**

White high-density polyethylene diffuser  
 Marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy

**NRTL** listed to North American Standards, suitable for wet locations  
 Protection class IP 65

**Weight:** 25.4 lbs.

**EPA (Effective projection area):** 1.1 sq. ft.

**Electrical**

Operating voltage	120-277VAC
Minimum start temperature	-30° C
LED module wattage	25.2W
System wattage	30.0W
Controllability	0-10V dimmable
Color rendering index	Ra > 80
Luminaire lumens	2380lm
LED service life (L70)	60000hrs

**LED color temperature**

4000K (K4)  
 3500K (K35)  
 3000K (K3)  
 2700K (K27)

**BEGA** can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

**Finish**

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish, a fluoropolymer technology, provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL and custom color finishes provided in either polyester powder or liquid paint.

**Available colors**

Black (BLK)	Bronze (BRZ)
Silver (SLV)	White (WHT)
RAL:	CUS:

Type:

BEGA Product:

Project:

Modified:

**Available options**

CUS	Custom finish
FSC	Fusing
MGU	Marine grade undercoat
RAL	RAL finish

**Pole-top luminaire · Symmetric**

	LED	A	B
<b>B88263</b>	25.2W	27 1/2	12 5/8

