

**Application**

Factory sealed recessed wall luminaire designed to be installed in walls or other vertical or horizontal surfaces for both interior and exterior locations.

**Materials**

Clear safety glass with white ceramic coating  
 Corrosion-resistant 304 grade stainless steel  
 Stainless steel screw clamps  
 Aluminum installation housing  
 Pure anodized aluminum reflector

**NRTL** listed to North American Standards, suitable for wet locations  
 Protection class IP 67

**Weight:** 3.8 lbs.

**Electrical**

LED module wattage	0.7 W
System wattage	1.0 W
Color rendering index	Ra > 80
Luminaire lumens	19 lm
LED service life (L70)	60000 hrs

**LED color temperature**

4000K (K4)  
 3500K (K35)  
 3000K (K3)  
 2700K (K27)

**BEGA** can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

**Finish**

#4 brushed stainless steel. Custom colors are not available.



**Recessed wall luminaire · Location luminaire • 24V DC**

	LED	A	B	C
<b>B88302</b>	ADA 0.7 W	15 <sup>3</sup> / <sub>4</sub>	1 <sup>1</sup> / <sub>2</sub>	2 <sup>3</sup> / <sub>4</sub>

Type:

BEGA Product:

Project:

Modified:

**Available accessories**

B19580 Remote driver box · Static white  
 B19591 Remote driver box · Static white

See individual accessory spec sheet for details.

**Included (available for pre-shipment)**

BB8302LED Installation housing

