

**Application**

A ground mounted luminaire with low mounting height and 180° light distribution. The narrow beam light distribution is ideally suited for illuminating and grazing ground surfaces. Provided with mounting system that allows the luminaire to be adjusted independent of anchor bolt orientation.

**Materials**

Chemically hardended soda-lime glass  
 A380 aluminum alloy  
 High temperature silicone gasket  
 Glass collimator

**NRTL** listed to North American Standards, suitable for wet locations  
 Protection class IP 67

**Weight:** 6.0lbs.

**Electrical**

Operating voltage 120-277VAC  
 Minimum start temperature -30° C  
 LED module wattage 9.0W  
 System wattage 12.0W  
 Controllability 0-10V dimmable  
 Color rendering index Ra > 80  
 Luminaire lumens 145lm  
 LED service life (L70) 60000hrs

**LED color temperature**

4000K (K4)  
 3500K (K35)  
 3000K (K3)  
 2700K (K27)

**BEGA** can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

**Finish**

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish, a fluoropolymer technology, provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL and custom color finishes provided in either polyester powder or liquid paint.

**Available colors**

Black (BLK)	Bronze (BRZ)
Silver (SLV)	White (WHT)
RAL:	CUS:

Type:

BEGA Product:

Project:


Modified:

**Available options**

CUS	Custom finish
FSC	Fusing
MGU	Marine grade undercoat
RAL	RAL finish

**Included (available for pre-shipment)**

B79815	Anchorage kit
--------	---------------



**On-ground luminaire · 180° light output**

	LED	A	B
<b>B88360</b>	9.0W	6 <sup>3</sup> / <sub>4</sub>	7 <sup>1</sup> / <sub>2</sub>

