Application

Tapered round aluminum pole with fixed bell base. Useful for mounting pole-top luminaires, floodlights, banners, or other accessories. Consult a licensed structural engineer when specifying. Poles must be unwrapped when delivered and should not be allowed to sit in their packaging.

Materials & Specifications

Extruded aluminum

Covered handhole with hardware and grounding provisions provided 3" welded tenon

Anchor bolts conform to ASTM F1554 Grade 55 with L bend on one end and galvanized minimum 12" on threaded end

Anchor bolts provided with (2) hex nuts and (2) flat washers

Wall thickness: 0.118" Structural weight: 64.0 lbs

Maximum Luminaire Weight: 60 lbs

Finish

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish, a fluoropolymer technology, provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL and custom color finishes provided in either polyester powder or liquid paint.

Available colors

 Black (BLK)
 Bronze (BRZ)

 Silver (SLV)
 White (WHT)

 RAL:
 CUS:

Type:

BEGA Pole:

Location:

Quote or Sales Order:

Date:

Specifier:

Representative:

BEGA Luminaire:

Total Mounted EPA:

Total Mounted Weight:

Available options


CUS Custom finish

MGU Marine grade undercoat

RAL RAL finish

Included (available for pre-shipment)

898A Anchorage kit



	Α		B*		С				
B926	3"		17'		15 ⁷ / ₈ "				
Pole wind I	oad rating	9							
MPH	85	90	100	110	120	130	140	150	
EPA**	6.6	5.0	3.9	2.8	2.1	1.7	1.3	0.9	

^{*}Height is rounded to the nearest foot, for precise measurements see submittal drawing.
**Data above assumes grade level installation and a maximum luminaire weight of 60 lbs

BEGA 1000 BEGA Way, Carpinteria, CA 93013 (805) 684-0533 info@bega-us.com

