

Application

Tapered round aluminum pole with fixed bell base. Useful for mounting pole-top luminaires, floodlights, banners, or other accessories. Consult a licensed structural engineer when specifying. Poles must be unwrapped when delivered and should not be allowed to sit in their packaging.

Materials & Specifications

Extruded aluminum
 3" welded tenon
 Covered handhole with hardware and grounding provisions provided
 Anchor bolts conform to ASTM F1554 Grade 55 with L bend on one end and galvanized minimum 12" on threaded end
 Anchor bolts provided with (2) hex nuts and (2) flat washers

Wall thickness: 0.118"

Structural weight: 59.0lbs

Maximum Luminaire Weight: 60 lbs

Finish

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish, a fluoropolymer technology, provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL and custom color finishes provided in either polyester powder or liquid paint.

Available colors

Black (BLK)	Bronze (BRZ)
Silver (SLV)	White (WHT)
RAL:	CUS:

Type:
 BEGA Pole:
 Location:
 Quote or Sales Order:
 Date:
 Specifier:
 Representative:
 BEGA Luminaire:
 Total Mounted EPA:
 Total Mounted Weight:

Available options

CUS	Custom finish
MGU	Marine grade undercoat
RAL	RAL finish

Included (available for pre-shipment)

898A	Anchorage kit
------	---------------



Aluminum pole · Fixed bell base

	A	B*	C
B928	3"	14'	15 ⁷ / ₈ "

Pole wind load rating

MPH	85	90	100	110	120	130	140	150
EPA**	6.8	5.3	4.5	4.0	3.6	3.0	2.5	2.0

*Height is rounded to the nearest foot, for precise measurements see submittal drawing.
 **Data above assumes grade level installation and a maximum luminaire weight of 60 lbs.

BEGA 1000 BEGA Way, Carpinteria, CA 93013 (805) 684-0533 info@bega-us.com

