

*PER AASHTO 2013 WIND MAP **DATA ABOVE ASSUMES GRADE LEVEL INSTALLATION AND A MAXIMUM LUMINAIRE WEIGHT OF 60 LBS.

DISCLAIMER:

BEGA NORTH AMERICA WARRANTS THE SPECIFIC ANCHOR BOLTS & POLE COMBINATION ACCORDING TO THE PRODUCT NUMBER(S) AND DESCRIPTION(S). STRUCTURAL CHANGES TO THE POLE REQUESTED BY THE CUSTOMER INCLUDING CHANGES TO THE POLE LENGTH, MAY AFFECT THE COMPATIBLITY OF THE ANCHOR BOLTS AND CORRESPONDING POLES. BEGA NORTH AMERICA IS NOT RESPONSIBLE FOR THE INCOMPATIBILITY OF THE ANCHOR BOLTS AND POLES RESULTING FROM SUCH STRUCTURAL CHANGES WITHOUT REVIEW BY THE BEGA NORTH AMERICA ENGINEERING DEPARTMENT. THIS INCLUDES BUT IS NOT LIMITED TO; ANY LABOR CHARGES, CHARGES FOR REPLACEMENT MATERIALS, AND SHIPPING. FOR SAFETY REASONS, DO NOT MOUNT MORE THAN MORE THAN 60 LBS. POLE CAPACITIES ARE BASED UPON THE PROVISIONS OF AASHTO 2013 (LTS-6). ADEQUATE DRAINAGE MUST BE PROVIDED IN CONCRETE FOUNDATION OR GROUT. DO NOT SEAL THE BASE OF THE POLE. DUE TO STRUCTURAL REASONS, DO NOT INSTALL POLE WITHOUT FIXTURE OR OTHER APPROPRIATE WEIGHT ON THE TOP

BEGA

1000 BEGA Way, Carpinteria, California 93013

```
P (805) 684-0533 - www.bega-us.com
```

APPROVED:	DESCRIPTION:					
TYPE:	ALUMINUM POLE: FIXED BELL BASE					
PROPRIETARY AND CONFIDENTIAL		SIZE	PART NO.			REV
THE INFORMATION CONTAINED IN THIS DRAWING OF BEGA NORTH AMERICA, INC. ANY REPRODUCTION IN PART OR AS A WHOLE W	В	928			-	
PERMISSION OF BEGA NORTH AMERICA, INC. IS F	NOT 1	TO SCALE	09/18/2023	SHEE	ET 1 OF 1	

