

Application

A bollard with shielded asymmetric light distribution. Designed for effective lighting of landscapes, pathways, and open spaces from low mounting heights. The fully shielded design provides visual comfort while illuminating ground surfaces. Provided with mounting system that allows the luminaire to be adjusted independent of anchor bolt orientation. DarkSky Approved (2700K and 3000K only)

Materials

Clear safety glass
 Marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy
 Mechanically captive stainless steel fasteners
 Silicone applied robotically to casting, plasma treated for increased adhesion
 Galvanized steel anchorage
 Pure anodized aluminum reflector

NRTL listed to North American Standards, suitable for wet locations
 Protection class IP 65

Weight: 10.8lbs.

Electrical

Operating voltage	120, 240 or 277VAC
Minimum start temperature	-30° C
LED module wattage	11.6W
System wattage	14.0W
Controllability	0-10V dimmable
Color rendering index	Ra > 80
Luminaire lumens	1361 lm
LED service life (L70)	60000hrs

LED color temperature

4000K (K4)
 3500K (K35)
 3000K (K3) (DarkSky Approved)
 2700K (K27) (DarkSky Approved)


BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish, a fluoropolymer technology, provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL and custom color finishes provided in either polyester powder or liquid paint.

Available colors

Black (BLK)	Bronze (BRZ)
Silver (SLV)	White (WHT)
RAL:	CUS:



Bollard · Wide spread

	LED	A	B
B99056	11.6W	7 ⁵ / ₈	21 ⁵ / ₈

Type:
 BEGA Product:
 Project:
 Modified:

Available options

AMB	Amber LED
CUS	Custom finish
FSC	Fusing
MGU	Marine grade undercoat
RAL	RAL finish

Included (available for pre-shipment)

B79817	Anchorage kit
--------	---------------

