

Application

Unshielded light is ideally suited for the illumination of pathways, entrance areas, or in a garden or residential area. Provided with mounting system that allows the luminaire to be adjusted independent of anchor bolt orientation.

Materials

Clear safety glass with white ceramic coating
 Marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy
 Silicone applied robotically to casting, plasma treated for increased adhesion
 Mechanically captive stainless steel fasteners

NRTL listed to North American Standards, suitable for wet locations
 Protection class IP 65

Weight: 17.9lbs.

Electrical

Operating voltage 120-277VAC
 Minimum start temperature -30° C
 LED module wattage 11.4 W
 System wattage 19.0 W
 Controllability 0-10V dimmable
 Color rendering index Ra > 80
 Luminaire lumens 751 lm
 LED service life (L70) 60000 hrs

LED color temperature

4000K (K4)
 3500K (K35)
 3000K (K3)
 2700K (K27)


BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish, a fluoropolymer technology, provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL and custom color finishes provided in either polyester powder or liquid paint.

Available colors

Black (BLK) Bronze (BRZ)
 Silver (SLV) White (WHT)
 RAL: CUS:



Bollard · Light emission on one side

	LED	A	B	C	D
B99326	11.4 W	4 ³ / ₄	39 ³ / ₈	3 ¹ / ₈	6 ³ / ₈

BEGA 1000 BEGA Way, Carpinteria, CA 93013 (805) 684-0533 info@bega-us.com

Type:
 BEGA Product:
 Project:
 Modified:

Available options

CUS Custom finish
 FSC Fusing
 MGU Marine grade undercoat
 RAL RAL finish

Included (available for pre-shipment)

B79817 Anchorage kit

