

Application

Bollard luminaire with shielded light distribution that is ideal for providing a high level of illuminance directly in front of the luminaire while providing exceptional glare control. Provided with mounting system that allows the luminaire to be adjusted independent of anchor bolt orientation.

Materials

Clear safety glass
 Marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy
 High temperature silicone gasket
 Self-expanding sleeve anchors for pre-cast concrete
 Pure anodized aluminum reflector

NRTL listed to North American Standards, suitable for wet locations
 Protection class IP 65

Weight: 8.8lbs.

Electrical

Operating voltage 120-277VAC
 Minimum start temperature -30° C
 LED module wattage 6.3W
 System wattage 9.0W
 Controllability 0-10V dimmable
 Color rendering index Ra > 80
 Luminaire lumens 444lm
 LED service life (L70) 60000hrs

LED color temperature

4000K (K4)
 3500K (K35)
 3000K (K3)
 2700K (K27)


BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish, a fluoropolymer technology, provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL and custom color finishes provided in either polyester powder or liquid paint.

Available colors

Black (BLK) Bronze (BRZ)
 Silver (SLV) White (WHT)
 RAL: CUS:



Bollard · Directed light · asymmetric

	LED	A	B	C
B99554	6.3W	6 ³ / ₈	31 ¹ / ₂	4 ³ / ₈

Type:

BEGA Product:

Project:

Modified:

Available options

CUS Custom finish
 MGU Marine grade undercoat
 RAL RAL finish

