

**Application**

Bollard with shielded 360° light distribution. This luminaire is designed to provide rotationally symmetric illumination of ground surfaces. Provided with mounting system that allows the luminaire to be adjusted independent of anchor bolt orientation.

**Materials**

- Borosilicate glass
- Marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy
- High temperature silicone gasket
- Mechanically captive stainless steel fasteners
- Galvanized steel anchorage
- Pure anodized aluminum reflector

**NRTL** listed to North American Standards, suitable for wet locations  
Protection class IP 65

**Weight:** 26.8 lbs.

**Electrical**

LED module wattage	12.4 W
System wattage	15.0 W
Color rendering index	Ra > 80
Luminaire lumens	451 lm
LED service life (L70)	60000 hrs

**LED color temperature**

- 4000K (K4)
- 3500K (K35)
- 3000K (K3)
- 2700K (K27)

**BEGA** can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

**Finish**

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish, a fluoropolymer technology, provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL and custom color finishes provided in either polyester powder or liquid paint.

**Available colors**

Black (BLK)	Bronze (BRZ)
Silver (SLV)	White (WHT)
RAL:	CUS:

Type:

BEGA Product:

Project:


Modified:

**Available options**

CUS	Custom finish
FSC	Fusing
MGU	Marine grade undercoat
RAL	RAL finish

**Included (available for pre-shipment)**

B79818	Anchorage kit
--------	---------------



Bollard · 360° light output			
	LED	A	B
<b>B99578</b>	12.4 W	11 <sup>7</sup> / <sub>8</sub>	19 <sup>3</sup> / <sub>4</sub>

