

**Application**

Bollard tube provided with integrated 6.0W emergency lighting battery. Battery will operate fixture at 34% of full output for 90 minutes. Ambient temperature must not go below -20°C and must not exceed 55°C. BEGA system bollard tubes are designed for easy attachment to system bollard heads using an interlocking mechanism. An accompanying bollard head must be selected for proper installation

**Materials**

Marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy  
 Die-cast aluminum  
 Extruded aluminum  
 Interlocking stainless steel mounting mechanism for attachment of head and tube  
 Mechanically captive stainless steel fasteners  
 Pre-wired with 5-pole plug-in connectors for ease of installation  
 Galvanized steel anchorage

**NRTL** listed to North American Standards, suitable for wet locations  
 Protection class IP 65

**Weight:** 31.1 lbs.

**Finish**

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish, a fluoropolymer technology, provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL and custom color finishes provided in either polyester powder or liquid paint.

**Available colors**

Black (BLK)	Bronze (BRZ)
Silver (SLV)	White (WHT)
RAL:	CUS:

Type:

BEGA Product:

Project:

Modified:

**Available options**

CUS	Custom finish
MGU	Marine grade undercoat
RAL	RAL finish

**Included (available for pre-shipment)**

B79818 Anchorage kit



**System bollard tube · Integral emergency lighting battery**

	A	B
<b>B99636</b>	10 <sup>3</sup> / <sub>8</sub>	34 <sup>1</sup> / <sub>2</sub>

