

Application

BEGA system bollard luminaire tube with passive infrared motion sensor. BEGA system bollard tubes are designed for easy attachment to system bollard heads using an interlocking mechanism. An accompanying bollard head must be selected for proper installation.

Materials

Die-cast aluminum
 Extruded aluminum
 Marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy
 Mechanically captive stainless steel fasteners
 Interlocking stainless steel mounting mechanism for attachment of head and tube
 Galvanized steel anchorage

NRTL listed to North American Standards, suitable for wet locations
 Protection class IP 65

Weight: 15.2lbs.

Electrical

Operating voltage 120-277VAC
 Minimum start temperature -40° C
 Controllability AC/DC Converter

Finish

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish, a fluoropolymer technology, provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL and custom color finishes provided in either polyester powder or liquid paint.

Available colors

Black (BLK)	Bronze (BRZ)
Silver (SLV)	White (WHT)
RAL:	CUS:

Type:

BEGA Product:

Project:

Modified:

Available options

CUS	Custom finish
MGU	Marine grade undercoat
RAL	RAL finish

Included (available for pre-shipment)

B79818 Anchorage kit



System bollard tube · Integral PIR motion sensor

	A	B
B99658	7 1/2	32

